

Data Sheet / Wayne Helix[®] 6000 II CNG dispenser

Lower Greenhouse Gas Emissions

Fuel Compatibility

- Compressed Natural Gas (CNG)

Model Availability

- Orientation: Lane. Dual-sided or Single-Sided
- Grades available: 1
- Nozzles available: 1 to 4. Also available as a back-2-back model for up to 5 grades in total
- Hydraulic System: Remote Pressure
- Pressure banks: External or 1 to 3
- Hose Management: Light Hose Retraction (LHR)
- Density: up to 80 kg/min
- Standard capacity and ERDGAS options available: 250 / 300 bar

Hanging Hardware

- Nozzle Types: NGV1, NGV2
- Hose Sizes: 3/8", 1/2"

Hose Reach

- LHR: 4 meter reach

Electronics

- iGem pump computer

Displays

- Premium 7-6-5 LED with 1.15" digits

Totalizers

- Electromechanical 7-digit totalizers

Communication Protocol

- DART as standard. Other protocols available

Metering

- Mass flow meter

Branding

- Optional customized graphics

Materials

- Painted hot dipped galvanized steel frame
- Painted hot dipped galvanized steel cladding

Corrosion Protection

- C4 protection according to ISO12944-2:1998 as standard

Operating temperature

- From -25°C to +55°C as standard
- Optional low temperature kit option for extended temperature range -40°C to +60°C

Relative Humidity

- From 5% to 95%

IP Rating

- IP 54 electronic head

Certifications

- ATEX
- OIML
- MID
- LNE



DFS Worldwide Brands