



# Data Sheet / Tokheim Quantum® FS LPG dispenser

Fueling the Future With LPG

## Fuel Compatibility

- Liquefied Petroleum Gas (LPG)

## Model Availability

- Orientation: Island, Dual-sided or Single-sided
- Hydraulic system: Remote Pressure
- Grades available: 1
- Nozzles available: 1 or 2
- Hose Management: Hose Hook or Hose Mast
- Flow Rates available: 5-50 lpm (max 25 bar)

## Hose Reach

- Hose Mast: 4.0 meter reach
- Hose Hook: 4.0 meter reach

## Electronics

- TQC pump computer

## Displays

- Premium 7-6-5 LED with 1.15" digits

## Totalizers

- Electromechanical 7-digit totalizers

## Communication Protocol

- IFSF as standard
- Other protocols available

## Metering

- GPL 700 meter

## Branding

- Optional customized graphics

## Materials

- Painted hot dipped galvanized steel frame
- Painted hot dipped galvanized steel cladding

## Corrosion Protection

- C4 protection according to ISO12944-2: 1998 as standard. Optional C5 protection available.

## Operating Temperature

- From -25°C to +55°C as standard
- Optional low temperature kit option for extended temperature range -40°C to +60°C

## Relative Humidity

- From 5% to 95%

## IP Rating

- IP 54 electronic head

## Certifications

- ATEX, OIML, MID



DFS Worldwide Brands



© 2024 Dover Fueling Solutions®. All rights reserved. DOVER®, the DOVER® D Design, DOVER FUELING SOLUTIONS®, and other trademarks referenced herein are trademarks of Delaware Capital Formation, Inc./Dover Corporation, Dover Fueling Solutions® UK Ltd. and their affiliated entities, registered or used in the United States and/or various other countries. 21.02.24