



Data Sheet / Tokheim Quantum[®] ML LPG Dispenser

Get into a Greener Gear with LPG

Fuel Compatibility

- Liquefied Petroleum Gas (LPG)

Model Availability

- Orientation: Lane, Dual-sided or Single-sided
- Grades available: 1
- Nozzles available: 1 to 2
- Hydraulic system: Remote Pressure
- Hose Management: Light Hose Retraction (LHR)
- Flow Rates available: 5-50 lpm (max 25 bar)

Hose Reach

- LHR: 3.9 meter reach

Electronics

- TQC pump computer

Displays

- Standard 6-6-4 LCD with 1.00" digits
- Premium 7-6-5 LED with 1.15" digits

Totalizers

- Electromechanical 7-digit totalizers

Communication Protocol

- IFSF LON as standard
- Other protocols available

Metering

- GPL700 meter

Branding

- Optional customized graphics

Materials

- Painted hot dipped galvanized steel frame
- Painted hot dipped galvanized steel cladding

Corrosion Protection

- C4 protection according to ISO12944-2: 1998 as standard. Optional C5 protection available

Operating Temperature

- From -25°C to +55°C as standard
- Optional low temperature kit option for extended temperature range -40°C to +60°C

Relative Humidity


- From 5% to 95%

IP Rating

- IP 54 electronic head

Certifications

- ATEX, OIML, MID



DFS Worldwide Brands



© 2024 Dover Fueling Solutions[®]. All rights reserved. DOVER[®], the DOVER[®] D Design, DOVER FUELING SOLUTIONS[®], and other trademarks referenced herein are trademarks of Delaware Capital Formation, Inc./Dover Corporation, Dover Fueling Solutions[®] UK Ltd. and their affiliated entities, registered or used in the United States and/or various other countries. 21.02.24