Site Efficiency
& Connectivity



We Believe in Choice.

ProGauge® Digimon LCD Console.

The Digimon LCD console is engineered to perform in all weather conditions. Featuring an LCD display, the console is perfectly designed to relay all of the necessary tank information in a succinct and immediately accessible manner. If you have only one tank to monitor, then this is all you need.

Visit Website

ProGauge®

Display.

- Backlit alphanumeric display, 16 x 2 lines
- Programming via configuration software

Housing.

- Explosion-proof, die-cast aluminum with epoxy coating
- 3 1/2” NPT-F threaded ports

Degree of Protection.

- IP67

Inputs.

- 1 RS485 serial port

Outputs.

- 1 RS485 serial port for data transmission
- 1 RS232 serial port for parameter configuration
- 4 NO/NC relay outputs

Visulaisation.

- Max. 1 probe (level from XMT explosion-proof probe - Exd)
- Product level in mm
- Actual volume in liters
- Compensated volume at 15°C in liters
- Product temperature
- Interface measurement and detection (presence of water at the bottom of the tank)
- Alarm signals

Power Input.

- 9÷30 VDC (in addition to internal 9V battery with measurement on request via a permanent magnet in case of power failure)

Certifications.

- ATEX
- UL-BR INMETRO



www.doverfuelingsolutions.com

©2026 Dover Fueling Solutions®. All rights reserved. DOVER®, the DOVER® D Design, DOVER FUELING SOLUTIONS®, and other trademarks referenced herein are trademarks of Delaware Capital Formation, Inc./Dover Corporation,Dover Fueling Solutions® UK Ltd. and their affiliated entities, registered or used in the United States and/or various other countries. 15.OCT.26.