Site Efficiency
& Connectivity

# Effortlessly Reliable.

## ProGauge® Level Monitor Console.

Small installations, such as home depots, maintenance garages and commercial fuelling locations, can be catered for using the Level Monitor. The entry-level console supports up to two, Ex certified probes and features a simple, user-friendly screen for fast access to tank gauge data.

Visit Website




ProGauge®

## Display.

- Backlit alphanumeric display, 20 x 2 lines
- Programming via configuration software

## Housing.

- Die-cast aluminum with epoxy coating
- 3 x 1/2 NPT-F threaded ports

## Degree of Protection.

- IP67

## Inputs.

- 2 x RS485 serial ports (supports up to 2 magnetostrictive probes)

## Outputs.

- 1 x RS232 serial port for parameter configuration
- 4 x NO/NC relay outputs

## Power Input.

- 9-30 Vdc / 220 Vac

## Certifications.

- CE mark

## Measurement.

- 2 x Tanks
- Product level in mm
- Actual volume in liters
- Compensated volume at 15°C in liters
- Tank level percentage
- Product temperature
- Interface measurement and detection (presence of water at the bottom of the tank)
- Alarm signals




www.doverfuelingsolutions.com

©2026 Dover Fueling Solutions®. All rights reserved. DOVER®, the DOVER® D Design, DOVER FUELING SOLUTIONS®, and other trademarks referenced herein are trademarks of Delaware Capital Formation, Inc./Dover Corporation,Dover Fueling Solutions® UK Ltd. and their affiliated entities, registered or used in the United States and/or various other countries. 15.OCT.26.