

Specifications and Features /

Wayne PWR™ DC fast charger

Relentless Reliability. Innovative Technology. Unwavering Consumer Experience.

Dover Fueling Solutions® brings quality, innovation, reliability and flexibility to EV charging with the Wayne PWR™ DC fast chargers. Designed and manufactured in the USA, the EV chargers are supported by a 135+ year legacy of excellence and feature a sleek, compact, NEVI-compliant design that is easy to maintain. Built for durability, they offer dependable performance across a range of temperatures, weather protection, vandal resistance, and UV and scratch-resistant finishes.

Serve a broader range of customers with our dual cable charger, supporting both CCS1 and NACS connectors at the charging point. Available power configurations: 640kW, 400kW, 240kW, 200kW & 160kW

POWER CABINET SPECIFICATIONS	
Part Numbers	DCC640 (Wayne PWR 640): powers 3 or 4 charging posts (DCP400) DCC400 (Wayne PWR 400), DCC240 (Wayne PWR 240), DCC200 (Wayne PWR 200) DCC160 (Wayne PWR 160): powers 1 or 2 charging posts (DCP400)
Load and Charging Management	Power cabinet has a dedicated group of power modules to each post, and dynamic groups that can combined to any post
AC Nominal Voltage (RMS)	480V ± 10% (Nominal rating)
Input AC Current @ 480V	DCC640: 850A (=4 posts), DCC400: 531A (≤ 2 posts), DCC240: 319A (≤ 2 posts), DCC200: 266A (≤ 2 posts), DCC160: 213A (≤ 2 posts)
Frequency	55~65Hz
Network Type	3-Phase Wye (TN-C)
Power Factor	≥ 0.99 @20~100% load
THDi (Total Harmonic Distortion)	<5%
Efficiency	≥ 94% @nominal output power
Connectivity	4G cellular, ethernet
Inlet Cable	4 per phase 250MCM-500MCM
Mounting	Free standing cabinet
Power Cabinet Noise Emissions	75 dB within 3 feet
Power Cabinet Dimensions (D x W x H)	Cabinet - 42 in. x 60 in. x 83 in. (1069 mm x 1524 mm x 2101 mm)
Power Cabinet Weight	Cabinet - Max 2500 lbs (1133 kg)

Specifications and Features / Wayne PWR™ DC fast charger

Relentless Reliability. Innovative Technology. Unwavering Consumer Experience.

CHARGING POST SPECIFICATIONS	
Model: DCP400	DCP400/xxxx*
Outputs	(1) per charging post
Cable Holster Location	Right-hand (for single cable only)
Max. Distance to Power Cabinet	328 feet (100 meters)
Charging Connection Options	CCS1 DC, NACS; available in single or dual cable configurations
Maximum Total DC Output Power	400kW - (640kW cabinet configuration) 320kW - (400kW cabinet configuration) 200kW - (240kW cabinet configuration) 160kW - (200kW cabinet configuration) 120kW - (160kW cabinet configuration)
Granularity of Output Power	40kW
Maximum Output Current	250A Continuous; 500A boost for limited duration
Output DC Voltage Range	150~1000VDC
Cable Length	13 ft (4 m)
Cable Retractor	Counter-weighted
User Interface	12-inch touchscreen display
LED Status Lights	Green (Available), Blue (Charging), Red (Off-line)
Mobile Payment	QR code or SMS
RFID Option	Dual-frequency (125/132 kHz & 13.56 MHz)
Payment System	EMV reader, Smart/Chip card reader, contactless reader with direct to host
Multilingual System	English (more options on request)
Receipt Type	Digital
Charging Post Noise Emissions	65 dB within 3 feet
Charging Post Dimensions (H x W x D)	Post - 19.2 in. x 26.5 in. x 82 in. (489 mm x 674 mm x 2085 mm)

* xxxx is placeholder for various option suffixes

Specifications and Features / Wayne PWR™ DC fast charger

Relentless Reliability. Innovative Technology. Unwavering Consumer Experience.

GENERAL OPERATIONAL SPECIFICATIONS	
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)
Operating Height	(6561 ft) 2000m
Environmental Conditions, in Storage	-22°F ~ 158°F `(-30°C ~ 70°C)
Environmental Conditions, Under Transport	-22°F ~ 158°F `(-30°C ~ 70°C)
Humidity (In Operation, Storage)	95% RH, non-condensing

NORMS, COMPLIANCE AND STANDARDS	
Communications Protocol for the Charging Infrastructure	OCPP 2.0.1
Vertical Inclination Angle	Max 5%
Protection Rating Enclosures (Cabinet and Post)	UL 3R
Eurofins Declaration of Conformity	UL 2202, UL 2594, UL 9741, UL 2231, UL 1741 3rd Ed., UL 50E
FCC Standards	FCC Part 15 Class A
Safety Design	Over/under voltage protection, overload protection, current leakage protection, grounding protection, over temp protection, lightning surge protection

